

TILTING DEAD BOLT, 92 mm BETWEEN AXES

194N RANGE



CHARACTERISTIC

- 16 mm, 22 mm or 24 mm SS flat front plate or 24,5x6 mm U shape SS front plate
- 11mm reversible latch bolt
- Adjustable latch and interchangeable by roller kit
- Prepared for bolt fixing handles and escutcheons
- 15 mm closed box
- 8mm square ruler
- 2 nylon escutcheons ref. ES1984
- Cylinder set screw

OPTIONAL ACCESSORIES

- Complete range of **strike plates**
- Complete range of **cylinders**
- **Electric strike plate** option
- Passing security escutcheon BTI296
- Roller kit to replace latch bolt (from 30mm backset on)
- Spindle adapter kit

DESCRIPTION	REF.	MEASUREMENTS		CAM	FINISH		UNITS
		B	A		FRONT PLATE	CYLINDER	

- Latch bolt and dead bolt
- Cylinder:
 - Long cam 101L3030/4

		P194N/25/6	22	37	15	Al	CN	1	20
		P194N/30/6	27	42	15	Al	CN	1	20
		P194N/35/6	32	47	15	Al	CN	1	20
		194N/25/6	22	37	15	Al	CN	1	20
		194N/30/6	27	42	15	Al	CN	1	20
		194N/35/6	32	47	15	Al	CN	1	20
		194N/25/6AN	22	37	15	Al	CN	1	20
		194N/30/6AN	27	42	15	Al	CN	1	20
		194N/35/6AN	32	47	15	Al	CN	1	20
		194N/25/6U	18	33	15	Al U	CN	1	20
		194N/30/6U	23	38	15	Al U	CN	1	20
		194N/35/6U	28	43	15	Al U	CN	1	20