


RIM DOOR LOCK 122 SERIES
SERIE 122C

CHARACTERISTICS

- Reinforced rim door lock
- Two turn, 4 bolt dead bolt operated by key from both sides of the sides
- Anti-crowbar system
- One turn dead bolt operated by key from both sides
- Two finishes: painted iron and nickel plated iron
- Strike plate for given locks
- Escutcheon for different cylinder types
- Fastening components


OPTIONAL ACCESSORIES

- Security european profile cylinder

DESCRIPTION
REF.
MEASUREMENTS CYLINDER
FINISH
UNITS
B
A
FRONT PLATE CYLINDER


- Profile cylinder ref. 5056/50/3
- Strike plate ref. CE122C/1 or CE122C/0
- Escutcheon ES125

122C70D/0	45	70	5056/50/3	HN	CL	1	10
122C70I/0	45	70	5056/50/3	HN	CL	1	10
122C70D/1	45	70	5056/50/3	HE	CL	1	10
122C70I/1	45	70	5056/50/3	HE	CL	1	10



- Round cylinder ref. 5156/50/3
- Strike plate ref. CE122C/1 or CE122C/0
- Escutcheon ES1125

1122C70D/0	45	70	5156/50/3	HN	CL	1	10
1122C70I/0	45	70	5156/50/3	HN	CL	1	10
1122C70D/1	45	70	5156/50/3	HE	CL	1	10
1122C70I/1	45	70	5156/50/3	HE	CL	1	10