RIM DOOR LOCK 56 SERIES

SERIE 56A



CHARACTERISTICS

- Latch bolt operated by key from outside and by key and pull handle from inside
- One turn dead bolt operated by key from both sides
- One turn dead bolt operated by key from both sides
- Two finishes: painted iron and nickel plated iron
- Strike plate for given locks
- Escutcheon for different cylinder types
- Fastening components

OPTIONAL ACCESSORIES

- Security european profile cylinder

DESCRIPTION	REF.	MEASUREMENTS B	MEASUREMENTS A	CYLINDER	FINISH FRONT PLATE	FINISH CYLINDER	UNITS	UNITS
• Profile cylinder ref. 5056/50/3 • Strike plate ref. CE56AD or CE56AI • Escutcheon ES125	56A60D/0	35	60	5056/50/3	HN	CL	1	24
	56A60I/0	35	60	5056/50/3	HN	CL	1	24
	56A60D/1	35	60	5056/50/3	HE	CL	1	24
	56A60I/1	35	60	5056/50/3	HE	CL	1	24
	56A70D/0	45	70	5056/50/3	HN	CL	1	24
	56A70I/0	45	70	5056/50/3	HN	CL	1	24
	56A70D/1	45	70	5056/50/3	HE	CL	1	24
	56A70I/1	45	70	5056/50/3	HE	CL	1	24
• Round cylinder ref. 5156/50/3 • Strike plate ref. CE56AD or CE56AI • Escutcheon ES1125	156A60D/0	35	60	5156/50/3	HN	CL	1	24
	156A60I/0	35	60	5156/50/3	HN	CL	1	24
	156A60D/1	35	60	5156/50/3	HE	CL	1	24
	156A60I/1	35	60	5156/50/3	HE	CL	1	24
	156A70D/0	45	70	5156/50/3	HN	CL	1	24
	156A70I/0	45	70	5156/50/3	HN	CL	1	24
	156A70D/1	45	70	5156/50/3	HE	CL	1	24
	156A70I/1	45	70	5156/50/3	HE	CL	1	24