


RIM DOOR LOCK 56 SERIES

SERIE 56B




CHARACTERISTICS

- Latch bolt operated by key from outside and by key and pull handle from inside
- One turn dead bolt operated by key from both sides
- One turn dead bolt operated by key from both sides
- Two finishes: painted iron and nickel plated iron
- Strike plate for given locks
- Escutcheon for different cylinder types
- Fastening components

OPTIONAL ACCESSORIES

- Security european profile cylinder

DESCRIPTION	REF.	MEASUREMENTS		CYLINDER	FINISH		UNITS	
		B	A		FRONT PLATE	CYLINDER		
• Profile cylinder ref. 5056/50/3	56B60D/0	35	60	5056/50/3	HN	CL	1	24
	56B60I/0	35	60	5056/50/3	HN	CL	1	24
• Strike plate ref. CE56AD or CE56AI	56B60D/1	35	60	5056/50/3	HE	CL	1	24
	56B60I/1	35	60	5056/50/3	HE	CL	1	24
• Escutcheon ES125	56BR70D/0	45	70	5056/50/3	HN	CL	1	24
	56BR70I/0	45	70	5056/50/3	HN	CL	1	24
	56BR70D/1	45	70	5056/50/3	HE	CL	1	24
	56BR70I/1	45	70	5056/50/3	HE	CL	1	24



• Round cylinder ref. 5156/50/3	156B60D/0	35	60	5156/50/3	HN	CL	1	24
	156B60I/0	35	60	5156/50/3	HN	CL	1	24
• Strike plate ref. CE56AD or CE56AI	156B60D/1	35	60	5156/50/3	HE	CL	1	24
	156B60I/1	35	60	5156/50/3	HE	CL	1	24
• Escutcheon ES1125	156BR70D/0	45	70	5156/50/3	HN	CL	1	24
	156BR70I/0	45	70	5156/50/3	HN	CL	1	24
	156BR70D/1	45	70	5156/50/3	HE	CL	1	24
	156BR70I/1	45	70	5156/50/3	HE	CL	1	24