


CHARACTERISTIC

- Nickel plated iron or stainless steel front plate
- Bichromate treated sides
- Tilting hook dead bolt
- Reversible latch bolt
- 8mm square ruler
- European profile cylinder
- 2 nylon escutcheons ref. ES1984
- Cylinder set screw

OPTIONAL ACCESSORIES

- Complete range of cylinders

DESCRIPTION	REF.	MEASUREMENTS			FINISH		UNITS	
		B	A	CAM	FRONT PLATE	CYLINDER		
<ul style="list-style-type: none"> • Latch bolt and dead bolt • Cylinder 101C3030 or 101L3030 • Strike plate CE1990/0 <p>Electric strike plate options</p> <ul style="list-style-type: none"> • CELC45/6A or CELC45/6AD 	1990/20/0	20	33	13,25	HN	CN	1	20
	1990/20/5	20	33	13,25	HN	CL	1	20
	1990/20/6	20	33	13,25	Al	CN	1	20
	1990/25/0	25	38	13,25	HN	CN	1	20
	1990/25/5	25	38	13,25	HN	CL	1	20
	1990/25/6	25	38	13,25	Al	CN	1	20
	1990/32/0	32	47	15	HN	CN	1	20
	1990/32/5	32	47	15	HN	CL	1	20
	1990/32/6	32	47	15	Al	CN	1	20
	<ul style="list-style-type: none"> • Dead bolt only • Cylinder 101C3030 or 101L3030 • Strike plate CE1990/0 	1990A20/0	20	33	13,25	HN	CN	1
1990A20/5		20	33	13,25	HN	CL	1	20
1990A20/6		20	33	13,25	Al	CN	1	20
1990A25/0		25	38	13,25	HN	CN	1	20
1990A25/5		25	38	13,25	HN	CL	1	20
1990A25/6		25	38	13,25	Al	CN	1	20
1990A32/0		32	47	15	HN	CN	1	20
1990A32/5		32	47	15	HN	CL	1	20
<ul style="list-style-type: none"> • Adjustable roller and dead bolt • Cylinder 101C3030 or 101L3030 • Strike plate CE1990/0 	1990V20/0	20	33	13,25	HN	CN	1	20
	1990V20/5	20	33	13,25	HN	CL	1	20
	1990V20/6	20	33	13,25	Al	CN	1	20
	1990V25/0	25	38	13,25	HN	CN	1	20
	1990V25/5	25	38	13,25	HN	CL	1	20
	1990V25/6	25	38	13,25	Al	CN	1	20
	1990V32/0	32	47	15	HN	CN	1	20
	1990V32/5	32	47	15	HN	CL	1	20
1990V32/6	32	47	15	Al	CN	1	20	