


# SWING DOORS / PIVOT DOORS

## SLIDING DEAD BOLT, 85 mm BETWEEN AXES

## 1E5 RANGE *Soft*



### CHARACTERISTIC

- Maximum softness by means of gear mechanism
- 1 point lock with 22 mm and 24 mm SS flat front plate or 24,5\*6 "U" shape SS front plate
- 11 mm reversible and adjustable latch bolt
- Minimum stock: 3 versions in 1 lock (latch bolt/ roller/ dead bolt only)
- Sliding dead bolt
- Designed according to EN12209 and pr. EN15685
- Compatible with Ion/DIN or short cam cylinders
- 15mm closed box
- 8mm square ruler
- Cylinder set screw

### VERSIONS

- Roller kit to replace latch bolt (ref. CV1E5)

### OPTIONAL ACCESSORIES

- Complete range of **strike plates**
- Complete range of **cylinders**

DESCRIPTION	REF.	MEASUREMENTS		CAM	FINISH		UNITS
		B	A		FRONT PLATE	CYLINDER	

- Latch bolt and dead bolt
- Cylinder not included

		1E5/30/6	27	43	15/13,25	Al	1
		1E5/35/6	32	48	15/13,25	Al	1
		1E5/40/6	37	53	15/13,25	Al	1
		1E5/45/6	42	58	15/13,25	Al	1
		1E5/50/6	47	63	15/13,25	Al	1
		1E5/30/6AN	27	43	15/13,25	Al	1
		1E5/35/6AN	32	48	15/13,25	Al	1
		1E5/40/6AN	37	53	15/13,25	Al	1
		1E5/45/6AN	42	58	15/13,25	Al	1
		1E5/50/6AN	47	63	15/13,25	Al	1
		1E5/30/6U	23	39	15/13,25	Al	1
		1E5/35/6U	28	44	15/13,25	Al	1
		1E5/40/6U	33	49	15/13,25	Al	1
		1E5/45/6U	38	54	15/13,25	Al	1
		1E5/50/6U	43	59	15/13,25	Al	1