

# SWING DOORS / PIVOT DOORS

## SLIDING DEAD BOLT MULTIPOINT LOCK, 92mm BETWEEN AXES

## 2E2GB RANGE *Soft*



### CHARACTERISTIC

- Maximum softness by means of gear mechanism
- Multi point lock with 16 mm, 22 mm and 24 mm SS flat front plate or 24,5\*6 "U" shape SS front plate
- 1850mm long front plate
- 11mm reversible and adjustable latch bolt
- Up and down points with hook and bolt
- Minimum stock: 3 versions in 1 lock (latch bolt/ roller/ dead bolt only)
- Sliding dead bolt
- Designed according to EN12209 and pr. EN15685
- Compatible with lon/DIN or short cam cylinders
- 15mm closed box
- 8mm square ruler
- Cylinder set screw

### VERSIONS

- In option 2300 mm long front plate (4E2GB range)
- In option 1500 mm long front plate (5E2GB range)
- Roller kit to replace latch bolt (ref. CV1E5)

### OPTIONAL ACCESSORIES

- Complete range of **strike plates**
- Complete range of **cylinders**

DESCRIPTION	REF.	MEASUREMENTS		CAM	FINISH		UNITS
		B	A		FRONT PLATE	CYLINDER	
<ul style="list-style-type: none"> <li>• Latch bolt and dead bolt</li> <li>• Cylinder not included</li> </ul>	P2E2GB30/6	27	43	15/13,25	Al	1	
	P2E2GB35/6	32	48	15/13,25	Al	1	
	P2E2GB40/6	37	53	15/13,25	Al	1	
	P2E2GB45/6	42	58	15/13,25	Al	1	
	P2E2GB50/6	47	63	15/13,25	Al	1	
	2E2GB30/6L	27	43	15/13,25	Al	1	
	2E2GB35/6L	32	48	15/13,25	Al	1	
	2E2GB40/6L	37	53	15/13,25	Al	1	
	2E2GB45/6L	42	58	15/13,25	Al	1	
	2E2GB50/6L	47	63	15/13,25	Al	1	
	2E2GB30/6LAN	27	43	15/13,25	Al	1	
	2E2GB35/6LAN	32	48	15/13,25	Al	1	
	2E2GB40/6LAN	37	53	15/13,25	Al	1	
	2E2GB45/6LAN	42	58	15/13,25	Al	1	
	2E2GB50/6LAN	47	63	15/13,25	Al	1	
2E2GB30/6U	23	39	15/13,25	Al	1		
2E2GB35/6U	28	44	15/13,25	Al	1		
2E2GB40/6U	33	49	15/13,25	Al	1		
2E2GB45/6U	38	54	15/13,25	Al	1		
2E2GB50/6U	43	59	15/13,25	Al	1		