


EMERGENCY FUNCTION EUROPEAN PROFILE CYLINDER

J6 -601CDE RANGE WITH SHORT CAM



CHARACTERISTIC

- Emergency function european profile cylinder with 6 pins
- Cylinder body and rotor in brass
- Pin, counterpins and springs in stainless steel
- Anti drill pins in both sides of the body
- Anti-picking protection
- Certified in compliance to the norm UNE-EN1303:2016
- Durability: 100.000 cycles
- Classification:

1	6	0	B	0	C	5	0/D*
---	---	---	---	---	---	---	------

D*: Drilling and mechanical attacking resistance with KES4100 escutcheon

- 13.5 mm short cam
- Brass and nickel matt finishings available
- 5 keys
- **Dimensions from 40 to 160mm**

DESCRIPTION


REF.

MEASUREMENTS


FINISH

UNITS

A	B	C
---	---	---



- Double cylinder




**EMERGENCY
FUNCTION**

601CDE3030/3	31	31	62	LP	1
601CDE3030/4M	31	31	62	NM	1
601CDE3035/3	31	36	67	LP	1
601CDE3035/4M	31	36	67	NM	1
601CDE3040/3	31	41	72	LP	1
601CDE3040/4M	31	41	72	NM	1
601CDE3535/3	36	36	72	LP	1
601CDE3535/4M	36	36	72	NM	1
601CDE3045/3	31	46	77	LP	1
601CDE3045/4M	31	46	77	NM	1
601CDE3540/3	36	41	77	LP	1
601CDE3540/4M	36	41	77	NM	1
601CDE3050/3	31	51	82	LP	1
601CDE3050/4M	31	51	82	NM	1
601CDE3545/3	36	46	82	LP	1
601CDE3545/4M	36	46	82	NM	1
601CDE4040/3	41	41	82	LP	1
601CDE4040/4M	41	41	82	NM	1
601CDE3055/3	31	56	87	LP	1
601CDE3055/4M	31	56	87	NM	1
601CDE4045/3	41	46	87	LP	1
601CDE4045/4M	41	46	87	NM	1
601CDE3550/3	36	51	87	LP	1
601CDE3550/4M	36	51	87	NM	1
601CDE3060/3	31	61	92	LP	1
601CDE3060/4M	31	61	92	NM	1
601CDE3555/3	36	56	92	LP	1
601CDE3555/4M	36	56	92	NM	1
601CDE4050/3	41	51	92	LP	1
601CDE4050/4M	41	51	92	NM	1

EMERGENCY FUNCTION EUROPEAN PROFILE CYLINDER

J6 -601CDE RANGE WITH SHORT CAM

DESCRIPTION	REF.	MEASUREMENTS			FINISH	UNITS
		A	B	C		
	601CDE4545/3	46	46	92	LP	1
	601CDE4545/4M	46	46	92	NM	1
	601CDE3065/3	31	66	97	LP	1
	601CDE3065/4M	31	66	97	NM	1
	601CDE3560/3	36	61	97	LP	1
	601CDE3560/4M	36	61	97	NM	1
	601CDE4550/3	46	51	97	LP	1
	601CDE4550/4M	46	51	97	NM	1
	601CDE3070/3	31	71	102	LP	1
	601CDE3070/4M	31	71	102	NM	1
	601CDE3565/3	36	66	102	LP	1
	601CDE3565/4M	36	66	102	NM	1
	601CDE4060/3	41	61	102	LP	1
	601CDE4060/4M	41	61	102	NM	1
	601CDE4555/3	46	56	102	LP	1
	601CDE4555/4M	46	56	102	NM	1
	601CDE5050/3	51	51	102	LP	1
	601CDE5050/4M	51	51	102	NM	1
	601CDE4560/3	46	61	107	LP	1
	601CDE4560/4M	46	61	107	NM	1
	601CDE3080/3	31	81	112	LP	1
	601CDE3080/4M	31	81	112	NM	1
	601CDE4070/3	41	71	112	LP	1
	601CDE4070/4M	41	71	112	NM	1
	601CDE5060/3	51	61	112	LP	1
	601CDE5060/4M	51	61	112	NM	1
	601CDE5555/3	56	56	112	LP	1
	601CDE5555/4M	56	56	112	NM	1
	601CDE5065/3	51	66	117	LP	1
	601CDE5065/4M	51	66	117	NM	1
	601CDE3090/3	31	91	122	LP	1
	601CDE3090/4M	31	91	122	NM	1
	601CDE6060/3	61	61	122	LP	1
	601CDE6060/4M	61	61	122	NM	1
	601CDE30100/3	31	101	132	LP	1
	601CDE30100/4M	31	101	132	NM	1
	601CDE7070/3	71	71	142	LP	1
	601CDE7070/4M	71	71	142	NM	1
	601CDE7575/3	76	76	152	LP	1
	601CDE7575/4M	76	76	152	NM	1
	601CDE8080/3	81	81	162	LP	1
	601CDE8080/4M	81	81	162	NM	1



**EMERGENCY
FUNCTION**