


NEW

EMERGENCY FUNCTION EUROPEAN PROFILE CYLINDER

J6 -601LDE RANGE WITH LONG CAM



CHARACTERISTIC

- Emergency function european profile cylinder with 6 pins
- Cylinder body and rotor in brass
- Pin, counterpins and springs in stainless steel
- Anti drill pins in both sides of the body
- Anti-picking protection
- Certified in compliance to the norm UNE-EN1303:2016
- Durability: 100.000 cycles
- Classification:

1	6	0	B	0	C	5	0/D*
---	---	---	---	---	---	---	------

D*: Drilling and mechanical attacking resistance with KES4100 escutcheon

- 15 mm long cam
- Brass and nickel matt finishings available
- 5 keys
- Dimensions from 40 to 160mm

DESCRIPTION

REF.

MEASUREMENTS


FINISH

UNITS


A B C



- Double cylinder

EMERGENCY
FUNCTION

	REF.	MEASUREMENTS			FINISH	UNITS
		A	B	C		
	601LDE3030/3	31	31	62	LP	1
	601LDE3030/4M	31	31	62	NM	1
	601LDE3035/3	31	36	67	LP	1
	601LDE3035/4M	31	36	67	NM	1
	601LDE3040/3	31	41	72	LP	1
	601LDE3040/4M	31	41	72	NM	1
	601LDE3535/3	36	36	72	LP	1
	601LDE3535/4M	36	36	72	NM	1
	601LDE3045/3	31	46	77	LP	1
	601LDE3045/4M	31	46	77	NM	1
	601LDE3540/3	36	41	77	LP	1
	601LDE3540/4M	36	41	77	NM	1
	601LDE3050/3	31	51	82	LP	1
	601LDE3050/4M	31	51	82	NM	1
	601LDE3545/3	36	46	82	LP	1
	601LDE3545/4M	36	46	82	NM	1
	601LDE4040/3	41	41	82	LP	1
	601LDE4040/4M	41	41	82	NM	1
	601LDE3055/3	31	56	87	LP	1
	601LDE3055/4M	31	56	87	NM	1
	601LDE4045/3	41	46	87	LP	1
	601LDE4045/4M	41	46	87	NM	1
	601LDE3550/3	36	51	87	LP	1
	601LDE3550/4M	36	51	87	NM	1
	601LDE3060/3	31	61	92	LP	1
	601LDE3060/4M	31	61	92	NM	1
	601LDE3555/3	36	56	92	LP	1
	601LDE3555/4M	36	56	92	NM	1
	601LDE4050/3	41	51	92	LP	1
	601LDE4050/4M	41	51	92	NM	1

EMERGENCY FUNCTION EUROPEAN PROFILE CYLINDER J6 -601LDE RANGE WITH LONG CAM


**EMERGENCY
FUNCTION**

DESCRIPTION	REF.	MEASUREMENTS			FINISH	UNITS
		A	B	C		
601LDE4545/3		46	46	92	LP	1
601LDE4545/4M		46	46	92	NM	1
601LDE3065/3		31	66	97	LP	1
601LDE3065/4M		31	66	97	NM	1
601LDE3560/3		36	61	97	LP	1
601LDE3560/4M		36	61	97	NM	1
601LDE4550/3		46	51	97	LP	1
601LDE4550/4M		46	51	97	NM	1
601LDE3070/3		31	71	102	LP	1
601LDE3070/4M		31	71	102	NM	1
601LDE3565/3		36	66	102	LP	1
601LDE3565/4M		36	66	102	NM	1
601LDE4060/3		41	61	102	LP	1
601LDE4060/4M		41	61	102	NM	1
601LDE4555/3		46	56	102	LP	1
601LDE4555/4M		46	56	102	NM	1
601LDE5050/3		51	51	102	LP	1
601LDE5050/4M		51	51	102	NM	1
601LDE4560/3		46	61	107	LP	1
601LDE4560/4M		46	61	107	NM	1
601LDE3080/3		31	81	112	LP	1
601LDE3080/4M		31	81	112	NM	1
601LDE4070/3		41	71	112	LP	1
601LDE4070/4M		41	71	112	NM	1
601LDE5060/3		51	61	112	LP	1
601LDE5060/4M		51	61	112	NM	1
601LDE5555/3		56	56	112	LP	1
601LDE5555/4M		56	56	112	NM	1
601LDE5065/3		51	66	117	LP	1
601LDE5065/4M		51	66	117	NM	1
601LDE3090/3		31	91	122	LP	1
601LDE3090/4M		31	91	122	NM	1
601LDE6060/3		61	61	122	LP	1
601LDE6060/4M		61	61	122	NM	1
601LDE30100/3		31	101	132	LP	1
601LDE30100/4M		31	101	132	NM	1
601LDE7070/3		71	71	142	LP	1
601LDE7070/4M		71	71	142	NM	1
601LDE7575/3		76	76	152	LP	1
601LDE7575/4M		76	76	152	NM	1
601LDE8080/3		81	81	162	LP	1
601LDE8080/4M		81	81	162	NM	1