


SLIDING DEAD BOLT, 85 mm BETWEEN AXES

1E5 RANGE *Soft*



CHARACTERISTIC

- Maximum softness by means of gear mechanism
- 1 point lock with 22 mm and 24 mm SS flat front plate or 24,5*6 "U" shape SS front plate
- 11 mm reversible and adjustable latch bolt
- Minimum stock: 3 versions in 1 lock (latch bolt/ roller/ dead bolt only)
- Sliding dead bolt
- Designed according to EN12209 and pr. EN15685
- Compatible with Ion/DIN or short cam cylinders
- 15mm closed box
- 8mm square ruler
- Cylinder set screw

VERSIONS

- Roller kit to replace latch bolt (ref. CV1E5)

OPTIONAL ACCESSORIES

- Complete range of **strike plates**
- Complete range of **cylinders**

DESCRIPTION	REF.	MEASUREMENTS		CAM	FINISH		UNITS
		B	A		FRONT PLATE	CYLINDER	

- Latch bolt and dead bolt
- Cylinder not included

		1E5/30/6	27	43	15/13,25	Al	1
		1E5/35/6	32	48	15/13,25	Al	1
		1E5/40/6	37	53	15/13,25	Al	1
		1E5/45/6	42	58	15/13,25	Al	1
		1E5/50/6	47	63	15/13,25	Al	1
		1E5/30/6AN	27	43	15/13,25	Al	1
		1E5/35/6AN	32	48	15/13,25	Al	1
		1E5/40/6AN	37	53	15/13,25	Al	1
		1E5/45/6AN	42	58	15/13,25	Al	1
		1E5/50/6AN	47	63	15/13,25	Al	1
		1E5/30/6U	22,5	38,5	15/13,25	Al	1
		1E5/35/6U	27,5	43,5	15/13,25	Al	1
		1E5/40/6U	32,5	48,5	15/13,25	Al	1
		1E5/45/6U	37,5	53,5	15/13,25	Al	1
		1E5/50/6U	42,5	58,5	15/13,25	Al	1